


[Click here to come back to the previous page](#)

MAIN INPUT DATA FILE : 2D HEAT-DRIVEN CAVITY FLOW

DIMENSIONLESS FORM :

$Ra = 1.D+06$
 Density scale : ρ_0 (fluid density)
 Length scale H : height of cavity
 Velocity scale $U_0 = (k/H).Ra^{0.25}$ (k thermal diffusivity)
 Temperature scale $Th - Tc$ ($Th = T_{hot}$; $Tc = T_{cold}$)
 Dimensionless Velocity $U^* = U/U_0$
 Dimensionless Temperature $T^* = (T - Tc)/(Th - Tc)$
 dimensionless kinematic viscosity = ν/α
 dimensionless thermal diffusivity = α/ν
 dimensionless buoyancy term = $\beta(T - Tc)$
 dimensionless domain $Lx/H = 1$, $Ly/H = 1$
 $Pr/Ra^{0.5}$
 $1/Ra^{0.5}$
 $Pr.T^*$
 1

$Q_0 = 0$ (adiabatic)



```

=====
=====
+++++
GENERAL LAYOUT
+++++

```

&Version File_Version="VERSION2.0"/

=====

FLUID PROPERTIES
(DIMENSIONLESS FORM)

=====

&Fluid_Properties Heat_Transfer_Flow = .true. , Reference_Density= 1.0,
Reference_Temperature= 1.0 ,
Reference_Dynamic_Viscosity= 0.71D-03 ,
Prandtl = 0.71 ,
Thermal_Expansion_Coefficient= 1.0 /

=====

UNIFORM INITIALIZATION OF THE VELOCITY COMPONENTS AND TEMPERATURE
(DIMENSIONLESS FORM)

=====

&Velocity_Initialization I_Velocity_Reference_Value = 0.0 ,
J_Velocity_Reference_Value = 0.0 , K_Velocity_Reference_Value
= 0.0 /
&Temperature_Initialization Temperature_Reference_Value = 0.5 /

=====

GRAVITY
(DIMENSIONLESS FORM)

=====

&Gravity Gravity_Enabled= .true. , Gravity_Angle_IJ= 90.0 ,
Gravity_Angle_IK= 90.0 , Reference_Gravity_Constant= 0.71/

=====

DOMAIN FEATURES

=====

&Domain_Features Start_Coordinate_I_Direction= 0.00 ,
End_Coordinate_I_Direction= 1.00,
Start_Coordinate_J_Direction= 0.00 ,
End_Coordinate_J_Direction= 1.00,
Start_Coordinate_K_Direction= 0.00 ,
End_Coordinate_K_Direction= 0.00,
Cells_Number_I_Direction= 256
,Cells_Number_J_Direction=256 ,Cells_Number_K_Direction= 1,
Regular_Mesh= .true. /

+++++

++

DEFINITION OF BOUNDARY CONDITIONS

+++++

++

=====

=

WALL BOUNDARY CONDITION SETUP

```

=====
=

    &Heat_Wall_Boundary_Condition_Setup
        West_Heat_BC_Option = 0    ,   East_Heat_BC_Option = 0    ,
Back_Heat_BC_Option = 1    ,   Front_Heat_BC_Option = 1    ,   South_Heat_BC_Option
= 0    ,   North_Heat_BC_Option = 0,
        West_Wall_BC_Value= 1.0    ,   East_Wall_BC_Value= 0.0    ,
Back_Wall_BC_Value= 0.0    ,   Front_Wall_BC_Value= 0.0    ,   South_Wall_BC_Value=
0.0    ,   North_Wall_BC_Value= 0.0    ,
        End_of_Data_Block= .true.    /
=====
=
BORDER BOUNDARY CONDITIONS
=====
=

    &Border_Domain_Boundary_Conditions West_Border= 0    ,   East_Border= 0    ,
Back_Border= 0    ,   Front_Border= 0    ,   North_Border = 0    ,   South_Border = 0 /
+++++
++

                NUMERICAL METHODS
+++++
++
Navier-Stokes equations ---> BDF2 + 2nd order centered scheme , semi-
implicit
convection flux            ---> conservative form
Poisson                    ---> Relaxed Gauss-Seidel method + Multigrid

    &Numerical_Methods   Numerical_Scheme= 1    ,
                        Convective_Flux_Discretization_Type = 1    ,
Temperature_Advective_Flux_Discretization_Type = 1    ,
                        Explicit_Solving_of_Density           = 0    ,
Velocity_Correction_Enabled           = .true.,
                        Numerical_Method_Poisson_Equation     = 1    ,
Number_max_Grid= 5, Number_max_Cycle= 10    ,   Number_Iteration= 15    ,
                        Relaxation_Coefficient= 1.7    ,   Convergence_Criterion=
1.D-10 /
+++++
++
SIMULATION MANAGEMENT
+++++
++

The numerical time step is estimated by means of the CFL coefficient

    &Simulation_Management   Restart_Parameter= 0    ,
                        Steady_Flow_Stopping_Criterion_Enabled = .true.
, Steady_Flow_Stopping_Criterion = 1.D-16,
                        Temporal_Iterations_Number = 1000000

```

```
, Final_Time = 5.D+02 ,
                                TimeStep_Type = 0 ,
                                Timestep_Min = 1.D-03
, Timestep_Max = 1.D-03 ,
                                CFL_Min      = 0.5
, CFL_Max      = 0.5 ,
                                Iterations_For_Timestep_Linear_Progress= 1,
                                Simulation_Backup_Rate      = 1000
, Simulation_Checking_Rate = 101 /

=====
=
PROBES MANAGEMENT
=====
=

    NO PROBE

=====
=
FIELDS RECORDING DECLARATION
=====
=
    &Simulation_Management Fields_Recording_Rate = 5.D+01 /
    &Field_Recording_Setup   Check_Special_Features=
"Heat_Driven_Cavity_Flow", Precision_On_Instantaneous_Fields= 2 / Here, a
special variable devoted to results of heat driven cavity flows is active

    &Instantaneous_Fields_Listing Name_of_Field = "U      " ,
Recording_Enabled = .true. /      First velocity component
    &Instantaneous_Fields_Listing Name_of_Field = "V      " ,
Recording_Enabled = .true. /      Second velocity component
    &Instantaneous_Fields_Listing Name_of_Field = "T      " ,
Recording_Enabled = .true. , End_of_Data_Block= .true. /      Temperature
```

[Click here to come back to the previous page](#)

From:
<https://sunfluidh.lisn.upsaclay.fr/> - Documentation du code de simulation numérique SUNFLUIDH

Permanent link:
https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:2d_heat_driven_cavity_incomp_flow&rev=1480499489

Last update: 2016/11/30 10:51

