



```
=====
INCOMPRESSIBLE FLUID FLOW --> Constant Density
HEAT DRIVEN FLOW          --> Activation of Heat Transfer
BOUSSINESQ ASSUMPTION     --> Thermal Expansion Coefficient = 1/T0 ( here
beta = 0 ==> beta = 1/T0 )

&Fluid_Properties   Variable_Density   = .false.   , Constant_Mass_Flow =
.true. , Heat_Transfer_Flow = .true. ,
                    Heat_Capacity_Ratio = 1.4 , Reference_Density= 1.225,
Reference_Dynamic_Viscosity= 1.852D-05,
                    Reference_Temperature= 300.0 , Prandtl = 0.707,
Reference_Heat_Capacity = 1004.D0 , Thermal_Expansion_coefficient = 0.0/
=====
    INITIALIZATION OF THE VELOCITY COMPONENTS, THE TEMPERATURE AND SPECIES
=====
    START FROM FLOW AT REST
    AND UNIFORM TEMPERATURE at T0 = 300 K

&Velocity_Initialization   I_Velocity_Reference_Value = 0.0 ,
J_Velocity_Reference_Value = 0.0 , K_Velocity_Reference_Value = 0.0 ,
                    Initial_Field_Option_For_Velocity_I = 0,
Initial_Field_Option_For_Velocity_J = 0 ,
Initial_Field_Option_For_Velocity_K = 0/

&Temperature_Initialization   Temperature_Reference_Value = 300.0,
Initial_Field_Option_For_Temperature = 0 /

=====
                                GRAVITY
=====
    FORCE GRAVITY ALONG THE VERTICAL AXIS POINTING DOWNWARD ( i.e. gravity = -
g.\vec{z} )
    CONSIDERING DIMENSIONAL PARAMETER g = 9.81 m/s^2

&Gravity   Gravity_Enabled= .true. , Gravity_Angle_IJ= 90.0 ,
Gravity_Angle_IK= 0.0 , Reference_Gravity_Constant= 9.81 /

=====
                                RADIATION
=====
    AS RADIATION IS CONSIDERED :
    - ACTIVATE THE RADIATIVE SOLVER [default = .false.] ( ONLY FOR 3D CARTESIAN
PROBLEMS !! )
    - SOLVE THE RADIATIVE PROBLEM EVERY 5 CONVECTIVE TIMESTEP ( LIMIT TIME
CONSUMPTION , KEEP THIS PARAMETER LOWER THAN 5~8 FOR STABILITY ... )
[default = 1]
    - IF STARTED FROM SCRATCH, FORCE THE SOLVER TO ITERATE OVER
FirstIterations=200 LOCAL ITERATIONS FOR INCIDENT FLUXES CONVERGENCES
    AT WALLS AND VOLUMIC RADIATIVE SOURCE TERM [default = 20]
    - FOR EACH RADIATIVE PROBLEM SOLVING STEPS, ITERATE OVER
```

```

RadiativeLocalIterations=20 SUB-ITERATIONS OR UNTIL
RadiativeConvergenceTolerance=5.E-05 RESIDUAL
  ERROR IS REACHED [default = 1.E-15]
  - WallRadCoeff AND VolRadCoeff ARE FOR DEVELOPPEMENT ONLY ... [default = 1]
  - CONSIDER THE "LATHROP" SCHEME TO INTERPOLATE THE CELL-FACES RADIATIVE
  INTENSITY [default = STEP]
  - CONSIDER THE ANGULAR DISCRETISATION WITH S10 LEVEL SYMMETRIC QUADRATURES
  Squad = 10 ( 120 DIRECTIONS IN VOLUMES, 60 DIRECTIONS ON WALLS) [default =
  8]
  - CONSIDER BLACK WALLS ON DIRICHLET WALLS AND REFLECTIVE WALLS ON THE
  OTHERS [default = 0.1]
  - CONSIDER THE MEDIUM AS A REAL GAS MIXTURE :
    + ACTIVATE THE SLW MODEL ActivateGas=.true. [default = .false.]
    + SPLIT THE ABSORPTION COEFFICIENT DOMAIN IN 8 WEIGHTED SUM OF GRAY-GASES
  NbGas = 8 [default = 1]
    + ka_min AND ka_max REPRESENTS THE MINIMUM AND MAXIMUM RANGE OF THE
  ABSORPTION COEFFICIENT DOMAIN in m^{-1} [default = 0]
    + CONSIDERS THE MEDIUM AS AN AIR-H2O GAS MIXTURE WITH UNIFORM MOLAR
  FRACTION x = 0.02 [default = 0.07]

```

```

&Radiative_Heat_Transfer_DOM    activateRadiation=.true. , RadiativePeriod =
5, FirstIterations=200,
    RadiativeLocalIterations=20, RadiativeConvergenceTolerance =
5.E-05,
    WallRadcoeff = 1.0 , VolRadCoeff = 1.0, RadiativeScheme =
"LATHROP",
    ActivateGas=.true., NbGas = 8, ka_max=570., ka_min=6.3e-07,
    Pref=101325.0, spec='H2O',xaref=0.02, xaUniform=0.02,
    Squad = 10, WallEmissivity = 1.0 1.0 0.0 0.0 0.0 0.0 /

```

#### =====

#### NON DIMENSIONAL PARAMETERS

#### =====

```

AS RADIATION IS CONSIDERED :
- REFERENCE LENGTH H IS REQUIRED

```

```

&Nondimensionalization Equations_Form= 4 , Reynolds= 0.00, Rayleigh= 0.00
, Reference_Velocity= 0.022 ,
    Reference_Temperature_Range= 0.01, Reference_Length= 1.0 /

```

#### =====

#### DOMAIN FEATURES

#### =====

```

- CONSIDER HERE A CUBICAL CAVITY WITH WALL REFINED CELLS GIVEN IN SEPARATE
MESH FILES
- WE CONSIDERS AN MPI DOMAIN DECOMPOSITION PROBLEM ON 2x2x3 MPI PROCESSES

```

```

&Domain_Features Start_Coordinate_I_Direction= 0.00 ,
End_Coordinate_I_Direction= 1.00,
    Start_Coordinate_J_Direction= 0.00 ,
End_Coordinate_J_Direction= 1.00,

```

```
                Start_Coordinate_K_Direction= 0.00 ,
End_Coordinate_K_Direction= 1.00,
                Cells_Number_I_Direction= 40 ,Cells_Number_J_Direction= 40
,Cells_Number_K_Direction= 30,
                Number_OMP_Threads= 1,
                MPI_Cartesian_Topology= .true. ,
                Total_Number_MPI_Processes= 12,
                Max_Number_MPI_Proc_I_Direction= 2 ,
Max_Number_MPI_Proc_J_Direction= 2, Max_Number_MPI_Proc_K_Direction= 3,
                Regular_Mesh= .false. /

+++++
++
                DEFINITION OF BOUNDARY CONDITIONS
+++++
++
=====
=
                WALL BOUNDARY CONDITION SETUP
=====
=
- WE CONSIDER DIRICHLET TEMPERATURE CONDITION ON HOT AND COLD WALLS
(Heat_BC_Option = 0)
- AND WALL CONVECTION-RADIATION COUPLING AT THE OTHER WALLS (Heat_BC_Option
= 6)

&Heat_Wall_Boundary_Condition_Setup
    West_Heat_BC_Option = 0 , East_Heat_BC_Option = 0 ,
Back_Heat_BC_Option = 6 , Front_Heat_BC_Option = 6 , South_Heat_BC_Option =
6 , North_Heat_BC_Option = 6,
    West_Wall_BC_Value= 300.005 , East_Wall_BC_Value= 299.995 ,
Back_Wall_BC_Value= 0.0 , Front_Wall_BC_Value= 0.0 , South_Wall_BC_Value=
0.0 , North_Wall_BC_Value= 0.0 ,
    End_of_Data_Block= .true. /
=====
=
                BORDER BOUNDARY CONDITIONS
=====
=
    THE BORDER BOUNDARY CONDITIONS HAVE ALREADY BEEN DEFINED ==> Border = 0

&Border_Domain_Boundary_Conditions West_Border= 0 , East_Border= 0 ,
Back_Border= 0 , Front_Border= 0 , North_Border = 0 , South_Border = 0 /
+++++
++
                NUMERICAL METHODS
+++++
++
    PARTIAL DIAGONALISATION TECHNIQUE IS EMPLOYED FOR THE POISSON PROBLEM ==>
Numerical_Method_Poisson_Equation    = 3
```

```

&Numerical_Methods Numerical_Scheme= 1 ,
                    Convective_Flux_Discretization_Type = 1 ,
Temperature_Advective_Flux_Discretization_Type = 1 ,
Species_Advective_Flux_Discretization_Type= 1 ,
                    Explicit_Solving_of_Density          = 0 ,
Velocity_Correction_Enabled          = .true.,
                    Numerical_Method_Poisson_Equation    = 3 ,
Iterative_Method_Selection            = 1 ,
                    Number_max_Grid= 4 ,
Number_max_Cycle= 10 , Number_Iteration= 15,
                    Relaxation_Coefficient              = 1.80 ,
Convergence_Criterion = 1.D-08 /
++++
++
SIMULATION MANAGEMENT
++++
++
- START FROM SCRATCH IF Restart_Parameter= 0 OR FROM EXISTING FILES IF
Restart_Parameter= 3
- WE CONSIDERS THAT THE PROBLEM WILL REACH A STEADY STATE AND WILL EVOLVE
IN TIME WITH FIXED CFL PARAMETER

&Simulation_Management Restart_Parameter= 3 ,
                        Steady_Flow_Stopping_Criterion_Enabled = .true. ,
Steady_Flow_Stopping_Criterion = 1.D-14,
                        Temporal_Iterations_Number = 100 , Final_Time =
3.D+04 ,
                        TimeStep_Type = 1 ,
                        CFL_Min        = 0.3 , CFL_Max        = 0.3 ,
                        Timestep_Min = 1.D-03 , Timestep_Max = 1.D+01 ,
                        Iterations_For_Timestep_Linear_Progress= 1,
                        Probe_Recording_Rate          = 1000
,
                        Simulation_Backup_Rate        = 5000 ,
Simulation_Checking_Rate = 20 /

=====
=
PROBES MANAGEMENT
=====
=
=====
=
FIELDS RECORDING DECLARATION
=====
=
&Field_Recording_Setup Check_Special_Features=
"NOHeat_Driven_Cavity_Flow" /
&Simulation_Management Fields_Recording_Rate = 5.D+02 /
&Instantaneous_Fields_Listing Name_of_Field = "U" , Recording_Enabled
= .true. / First velocity component

```

```
&Instantaneous_Fields_Listing Name_of_Field = "V      " , Recording_Enabled
= .true. /      Second velocity component
&Instantaneous_Fields_Listing Name_of_Field = "W      " , Recording_Enabled
= .true. /      Third velocity component
&Instantaneous_Fields_Listing Name_of_Field = "T      " , Recording_Enabled
= .true. /      Temperature
&Instantaneous_Fields_Listing Name_of_Field = "P      " , Recording_Enabled
= .true. /      Pressure
&Instantaneous_Fields_Listing Name_of_Field = "divU   " , Recording_Enabled
= .true. , End_of_Data_Block= .true. /      momentum divergence
```

From:  
<https://sunfluidh.lisn.upsaclay.fr/> - Documentation du code de simulation numérique SUNFLUIDH

Permanent link:  
[https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:3d\\_heat\\_driven\\_cavity\\_incomp\\_flow\\_gasrad&rev=1481631220](https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:3d_heat_driven_cavity_incomp_flow_gasrad&rev=1481631220)

Last update: 2016/12/13 13:13

