

[Click here to come back to the previous page](#)

grid file

[data_meshgen.dat](#)

```
=====
=====
=====
=====
DATA FILE FOR THE MESH GENERATOR MESHGEN (DESCRIPTIONS OF
DATA ARE GIVEN BELOW)
=====
=====
-----
-----
Blocks of data are associated to segments along a specific direction
(There are as many blocks as segments)
See below the TEMPLATES to select your own block of data associated to
the selected distribution law)
-----
-----
-----
I-DIRECTION
-----
Choice of the metric system : in meter or dimensionless (0) -
angular in degrees (1) :
&METRIC_UNIT Type_of_Metric= 0 /
&MESH_FUNCTION_DATA Function_Name="TANH_ONE_SIDE" Number_of_Cells= 32
Length= 0.01 Left_Cell_Size= 1.00d-04 Reverse_Ordering= .true. /
&MESH_FUNCTION_DATA Function_Name="REGULAR" Number_of_Cells=
200 Length= 0.0200 Reverse_Ordering= .false. /
&MESH_FUNCTION_DATA Function_Name="TANH_TWO_SIDES" Number_of_Cells=
280 Length= 0.09 Left_Cell_Size= 1.0d-04 Right_Cell_Size= 1.0d-04
Reverse_Ordering= .false. /
&MESH_FUNCTION_DATA End_of_Data_Block = .true./
-----
J-DIRECTION
-----
Choice of the metric system : in meter or dimensionless (0) -
angular in degrees (1) :
&METRIC_UNIT Type_of_Metric= 0 /
&MESH_FUNCTION_DATA Function_Name="TANH_ONE_SIDE" Number_of_Cells= 49
Length= 0.0141 Left_Cell_Size= 6.00d-05 Reverse_Ordering= .true. /
&MESH_FUNCTION_DATA Function_Name="REGULAR" Number_of_Cells= 15
Length= 9.e-4 Reverse_Ordering= .false. /
&MESH_FUNCTION_DATA End_of_Data_Block = .true./
-----
K-DIRECTION
-----
```

```
&MESH_FUNCTION_DATA End_of_Data_Block = .true./
```

```
-----
-----
                        DATA DESCRIPTION
-----
-----
```

Main setup file

[input3d.dat](#)

```
=====
=====
=====
=====

      MAIN INPUT DATA FILE :

      SUCCESSIVE COMPRESSION CYCLES OF A 2D QUASI-ADIABATIC CAVITY
      LMN APPORACH

      Wall Qh=0

      <-- | -->
      Wall Qh= 0
      T= T0 |
      <-----|----->

      Symmetric plan

      DIMENSIONAL SETUP

      fluid : air at P= 101325 Pa and T= 294.146 K (initial
condition at t=0)
      cavity size= 0.10m * 0.015m
      volume variation : A.sin(2pi.f.t- w0)      w0= pi/2
                        A= 0.01 m
                        f= 50 Hz

=====
=====
=====
=====

&Version File_Version="VERSION2.0"/
```

```

+++++
GENERAL LAYOUT
(DIMENSIONLESS)
+++++
&Fluid_Properties Variable_Density          = .true. ,
Constant_Mass_Flow      = .false. ,
                      Variable_Fluid_Volume= .true. ,
                      Molecular_Mass= 0.02896421357024561 ,
                      Heat_Transfer_Flow    = .true. ,
                      Reference_Dynamic_Viscosity = 1.795D-05,
                      Reference_Density      = 1.2 ,
                      Reference_Temperature  = 294.146 ,
                      Prandtl               = 0.726 ,
                      Reference_Heat_Capacity = 1004.7093960142244 ,
                      Heat_Capacity_Ratio    = 1.4 /

&Velocity_Initialization I_Velocity_Reference_Value = 0.0 ,
J_Velocity_Reference_Value = 0.0 , K_Velocity_Reference_Value = 0.0 /
&Temperature_Initialization Temperature_Reference_Value= 294.146 ,
Initial_Field_Option_For_Temperature= 0 /
=====
====

DOMAIN FEATURES
(DIMENSIONLESS)
=====
====
&Domain_Features Start_Coordinate_I_Direction=-0.020 ,
End_Coordinate_I_Direction= 0.10,
                  Start_Coordinate_J_Direction= 0.00 ,
End_Coordinate_J_Direction= 0.015,
                  Start_Coordinate_K_Direction= 0.00 ,
End_Coordinate_K_Direction= 0.00,
                  Cells_Number_I_Direction= 512
,Cells_Number_J_Direction= 64 ,Cells_Number_K_Direction= 1,
                  Regular_Mesh= .false. /
+++++
DEFINITION OF BOUNDARY CONDITIONS
+++++
=====
=====

WALL BOUNDARY CONDITION SETUP
(DIMENSIONLESS)
=====
=====
=====
=====

```

INLET AND OUTLET BOUNDARY CONDITIONS (DIMENSIONLESS)

```
=====
=====

&Inlet_Boundary_Conditions  Type_of_BC= "INLET", Direction_Normal_Plan=
1 ,
                                Plan_Location_Coordinate= -0.0200 ,
                                Start_Coordinate_of_First_Span = 0.00 ,
End_Coordinate_of_First_Span = 0.015 ,
                                Start_Coordinate_of_Second_Span= 0.0 ,
End_Coordinate_of_Second_Span= 0.0 ,
                                Flow_Direction= 1 ,
                                Define_Velocity_Profile= 0,
                                Normal_Velocity_Reference_Value= 0.0 ,
                                Temperature_Reference_Value= 294.146 ,
                                Density_Reference_Value= 1.2 ,
                                Temperature_BC_Type="Neumann",
                                Density_BC_Type="Neumann",
                                Variable_Flowrate= 0/
                                !Time_Fct_Name= "Sinus_zero_average" ,
Time_Fct_Threshold= 0.0 ,
                                !Time_Fct_Time_Scale= 2.0E-02 ,
Time_Fct_Magnitude= 4.712 /
```

IMMERSED BOUNDARY METHODS : PENALIZATION METHOD

```
=====
=====

&Immersed_Boundary_Methods  Immersed_Boundary_Method_Type= 1 ,
                                Name_of_Solid="RECTANGLE",
                                Linked_IBM_Inlet_Number = 1 ,
                                Gravity_IBM_Enabled = .false. ,
                                StrongPenaltyForVelocity_Enabled=.true.,
                                Coordinate_Gravity_Center_At_Rest_I=-0.04 ,
Coordinate_Gravity_Center_At_Rest_J= 0.0075 ,
Coordinate_Gravity_Center_At_Rest_K= 0.0 ,
                                Coordinate_Gravity_Center_Init_I= -0.05 ,
Coordinate_Gravity_Center_Init_J= 0.0075 ,
Coordinate_Gravity_Center_Init_K= 0.0 ,
                                Coordinate_Restricted_Motion_I=-0.04 ,
Coordinate_Restricted_Motion_J= 0.0 , Coordinate_Restricted_Motion_K=
0.0 ,
                                Size_Object_I= 0.08 ,
Size_Object_J= 0.015 , Size_Object_K= 0.0 ,
                                Reference_Velocity_I= 0.0 ,
Reference_Velocity_J= 0.0 , Reference_Velocity_K= 0.0 ,
```

```

Motion_Magnitude_I= 0.010
, Motion_Magnitude_J= 0.00 , Motion_Magnitude_K= 0.0
,
Mass= 1.2 ,
Spring_Stiffness_Constant_I= 0.0 ,
Spring_Stiffness_Constant_J= 0.0 , Spring_Stiffness_Constant_K=
0.0 ,
Transitional_Time= 0.00, Forced_Frequency=
5.0D+01 , OffSet= 0.5,
Heat_Transfer_Type= 0,
Reference_Temperature= 294.146 ,
Reference_Heat_Flux= 0.0 ,
Material_Thermal_Conductivity= 2.4841D-02 ,
Material_Mass_Heat_Capacity= 1004.7094, Material_Density= 1.2 /

=====
=====
ENDS BOUNDARY CONDITIONS
=====
=====
&Border_Domain_Boundary_Conditions West_BC_Name = "None" ,
East_BC_Name = "None" ,
Back_BC_Name = "Symmetric" ,
Front_BC_Name = "None" ,
North_BC_Name = "None" ,
South_BC_Name = "None" /
+++++
+++++
NUMERICAL METHODS
+++++
+++++
&Numerical_Methods
!!!NS_NumericalMethod= "BDF2-Scheme02",
NS_NumericalMethod= "CN-Scheme02",
!!!NS_NumericalMethod= "CN-Scheme02-
SpecialLowMachFlow",
!!!MomentumConvection_Scheme="Centered-02-
Conservative" ,
MomentumConvection_Scheme="Centered-02-
Convective_2" ,
!!!MomentumConvection_Scheme="Upwind-01-
Convective" ,
TemperatureAdvection_Scheme="Centered-02-
Convective_2" ,
!!!TemperatureAdvection_Scheme="Upwind-01-
Convective" ,
!!!TemperatureAdvection_Scheme="Centered-02-
Convective" ,
!Poisson_NumericalMethod="Home-
PartialDiagonalization" ,
!Poisson_NumericalMethod="Home-SORMultigrid-

```

```

ConstantMatrixCoef" ,
                        Poisson_NumericalMethod="Home-SORMultigrid-
VariableMatrixCoef" ,
                        Off_Set_Poisson_Source_term= .true./

!HomeData_PoissonSolver
    Direction_1= 2,
    Direction_2= 1,
    Direction_3= 3/

&HomeData_PoissonSolver SolverName="SOR" ,!Successive Over-
Relaxation (SOR) method based on the red-black algorithm
                        MultiGrid_Type="V_Cycle",
                        Relaxation_Coefficient= 1.45 ,!Relaxation
coefficient of the SOR method ( 1 <= Relaxation_Coefficient < 2)
                        Number_max_Grid= 7 ,!Number of grid
levels
                        Number_max_Cycle= 9
                        Number_Iteration_FineToCoarseGrid=3 ,!number
of SOR iterations applied on any grid level during the restriction step
(before the coarsest grid computation)
                        Number_Iteration_CoarseToFineGrid= 15 ,!number
of SOR iterations applied on any grid level during the prolongation
step (after the Coarsest grid computation)
                        Number_Iteration_CoarsestGrid= 30 ,!number of
SOR iterations applied on the coarsest grid
                        ResidualNormalisation_Enabled= .true.,
                        ConvergenceStrengthening_Enabled= .true. ,
                        Convergence_Criterion= 1.D-04
/!convergence tolerance on the residu of the Poisson's equation

+++++
+++++
                        SIMULATION MANAGEMENT
+++++
+++++
The numerical time step is dynamic and is estimated by the constant CFL
coefficient

&Simulation_Management Restart_Parameter= 0 ,
                        Steady_Flow_Stopping_Criterion_Enabled =
.true. , Steady_Flow_Stopping_Criterion = 1.D-16,
                        Temporal_Iterations_Number = 4000000
, Final_Time = 4.00D-00 ,
                        TimeStep_Type = 0 ,
                        TimeStep_Max = 1.0D-05,
                        CFL_Max = 0.3 ,
                        Simulation_Backup_Rate = 1000
, Simulation_Checking_Rate = 101 /
=====

```

```

=====
                                PROBES MANAGEMENT
=====
=====

&Simulation_Management    Probe_Recording_Rate = 100      /

&Probe_Quantities_Enabled Temporal_Series_For_Quantity_Enabled(:)=
.true. , .true., .false., .false., .false., .false. /

&Probe_Location   Xi=-0.011 , Xj= 0.007 , Xk= 0.0 /

=====
=====
                                FIELDS RECORDING DECLARATION
=====
=====

!-----
!--- Instantaneous fields
!-----

&Field_Recording_Setup    Precision_On_Instantaneous_Fields= 1 /
&Simulation_Management    InstantaneousFields_TimeRecordingRate =
1.0D-03 InstantaneousFields_RecordingStartTime=0.0 /

&Instantaneous_Fields_Listing Name_of_Field = "U      " /      First
velocity component
&Instantaneous_Fields_Listing Name_of_Field = "V      " /      Second
velocity component
&Instantaneous_Fields_Listing Name_of_Field = "P      " /
&Instantaneous_Fields_Listing Name_of_Field = "T      " /
&Instantaneous_Fields_Listing Name_of_Field = "TRACE " /
&Instantaneous_Fields_Listing Name_of_Field = "RHO   " /
!Instantaneous_Fields_Listing Name_of_Field = "divU  " /
!Instantaneous_Fields_Listing Name_of_Field = "divRU " /
!Instantaneous_Fields_Listing Name_of_Field = "PHI   " /
!Instantaneous_Fields_Listing Name_of_Field = "drho  " /
!Instantaneous_Fields_Listing Name_of_Field = "SRC_P " /

!-----
!--- Statistic fields
!-----

&Simulation_Management    Start_Time_For_Statistics= 2.D-01
, Time_Range_Statistic_Calculation = 3.8D-01 /

&Statistical_Fields_Listing Name_of_Field = "<U>    " /
&Statistical_Fields_Listing Name_of_Field = "<V>    " /
&Statistical_Fields_Listing Name_of_Field = "<T>    " /
&Statistical_Fields_Listing Name_of_Field = "<P>    " /

```

```
&Statistical_Fields_Listing Name_of_Field = "<Rho> " /

!-----
!--- Time series
!-----
&Time_Series_Data Title= "MassFlowBalance" , Filename= "check_mass.dat"
, iter_rec= 10 ,
                Time_Start_Mean_Calculation= 40.
,Range_Mean_Calculation= 80.
                Restart_Enabled= .false. /

&Time_Series_Data Title= "VolumeFlowBalance" , Filename=
"check_vol.dat" , iter_rec= 10 ,
                Time_Start_Mean_Calculation= 40.
,Range_Mean_Calculation= 80.
                Restart_Enabled= .false. /

&Time_Series_Data Title= "LMN_Data" , Filename= "check_lmndata.dat" ,
iter_rec= 10 ,
                Time_Start_Mean_Calculation= 40.
,Range_Mean_Calculation= 80.
                Restart_Enabled= .false. /

&Time_Series_Data Title= "KE_Average" , Filename=
"check_kin_energy.dat" , iter_rec= 10 ,
                Time_Start_Mean_Calculation= 40.
,Range_Mean_Calculation= 80.
                Restart_Enabled= .false. /
```

[Click here to come back to the previous page](#)

From:

<https://sunfluidh.lisn.upsaclay.fr/> - **Documentation du code de simulation numérique SUNFLUIDH**

Permanent link:

https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:piston_motion2d_1&rev=1619631135

Last update: **2021/04/28 19:32**

