

Namelist "Slices_Recording_Setup"

This data set is used to define the position and the orientation of a slice on which different instantaneous fields of data will be recorded.

Full data set of the namelist

```
&Slices_Recording_Setup
  Identifier_Value=1, Normal_Direction_Index=1,
  Normal_Direction_Coordinate= 0.6 ,
  Field_Number= 2,
  List_Of_Fields= "U      " , "V      "/
```

Identifier_Value

- Type : Integer value
- Set the ID number of the slice

Normal_Direction_Index

- Type : Integer value
- Set the normal direction of the slice (I : 1 , J : 2 or K : 3)

Normal_Direction_Coordinate

- Type : Real value
- Set the position of the slice in the computational domain. The coordinate depends on the orientation of the slice.

Field_Number

- Type : Integer value
- Set the number of fields to consider.

List_Of_Fields

- Type : character string
- Set the name of fields to record on the slice (6 characters max.)

Last
update:
2019/12/25 13:08 sunfluidh:slices_recording_setup_namelist https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:slices_recording_setup_namelist&rev=1577275696

From:
<https://sunfluidh.lisn.upsaclay.fr/> - **Documentation du code de simulation numérique SUNFLUIDH**

Permanent link:
https://sunfluidh.lisn.upsaclay.fr/doku.php?id=sunfluidh:slices_recording_setup_namelist&rev=1577275696

Last update: **2019/12/25 13:08**

